




## ProSTUD® 3-5/8" STUD CHASE WALL SOUND ASSEMBLIES

STAGGERED IN 6" TRACK

Partition type	Assembly description		STC Rating / Test Report
			ProSTUD 25 (15mil)
	3-5/8" ProSTUD 3-1/2" R-13 unfaced insulation 1 layer 5/8" Type X GWB on each side	@16" o.c.	49 <a href="#">TL09-587</a>
	3-5/8" ProSTUD 3-1/2" R-13 unfaced insulation 1 layer 5/8" Type X GWB on one side 2 layers 5/8" Type X GWB on the other side	@16" o.c.	52 <a href="#">TL09-588</a>
	3-5/8" ProSTUD 3-1/2" R-13 unfaced insulation 2 layers 5/8" Type X GWB on each side	@16" o.c.	56 <a href="#">TL09-589</a>

### Notes:

- Sound assemblies are certified by Western Electro-Acoustic Laboratories.
- NVLAP accredited for ASTM E90 & E413, ISO Certified.
- See STC test reports at [www.clarkdietrich.com/ProSTUD](http://www.clarkdietrich.com/ProSTUD) for detailed requirements of construction of wall assembly. Contact ClarkDietrich Technical Services at 888-437-3244 for questions about ProSTUD sound assemblies.

Visit [itools.clarkdietrich.com](http://itools.clarkdietrich.com) for a complete list of sound ratings.