

FastBack™ Backing System (FBBC)

Reduces finishing time with no exposed fasteners on the face of the product.

The FastBack™ backing system features a universal design that works with studs in either direction—concealing fasteners on the face of the product. The system creates an interlocked design between the stud and track for baseboard backing installations; and a cutaway design allows backing and bracing to be installed all the way to the floor. Pre-cut and fire-rated, the Dricon® Wood Backing is sized to fit 12," 16" and 24" o.c. spacing. Available for overnight delivery.

PRODUCT DIMENSIONS

- 1-1/4" x 5-1/8"
- 1-1/4" x 10-1/4"

INSTALLATION

Rotate the FastBack clip over the flange of the stud until it sits flush. Fasten into place using drywall screws in the pre-drilled holes. Place wood onto tabs and fasten into place using standard drywall screws.



FastBack Backing System

FastBack™ BACKING SYSTEM

Product code	Width (in)	Length (in)	Packaging Pcs./Carton
FBBC	1-1/4	5-1/8	100
FBBC	1-1/4	10-1/4	100

Dricon® WOOD BACKING

Product code	Width (in)	Length (in)	Packaging Pcs./Skid
FBW	5-1/8	10-1/2	720
FBW	5-1/8	14-1/2	540
FBW	5-1/8	22-1/2	360
FBW	10-1/4	10-1/2	720
FBW	10-1/4	14-1/2	540
FBW	10-1/4	22-1/2	360

Dricon® is a registered trademark of Arch Wood Protection, Inc.



Dricon® FRT Wood complies with or has been granted the following:

AWPA C20/C27	UL Recognized Component
AWPA P17 (FR-1)	NYC MEA 199-81-M
FR-S	NYC MEA 200-81-M
NER-303 (BOCA, ICBO, SBCCI)	Factory Mutual Class I Roof Deck
EPA Registration (62190-9)	City of Los Angeles (RR 25122)
UL Building Materials Directory	FHA Minimum Property Standard #2600

U.S. Patent No. 7,882,676 of Jeffrey Thomas Ellis  
Dricon is a registered trademark of Arch Wood Protection, Inc.

HUD Materials Release (1261)  
California State Fire Marshal  
State of Wisconsin  
QPL  
  
All are subject to revision, reexamination.